



SOLAR CONTROL FILM

Reflective – Silver 50

SO-50RS-eSR

Opalux® Reflective Silver 50 solar control film offers good heat rejection for externally applied films, whilst still offering plenty of light through.

Opalux® Reflective Silver 50 solar control film can also provide additional benefits such as uniform outside appearance and as with most Opalux® films up to 99% ultraviolet light (UV) filtering. (For specialist UV filtering in museums etc, see Specialist UV Control Film). This film can help to reduce cooling costs and therefore Climate Change Levy liability by lightening the load on air conditioning equipment. Government and business organisations can use Opalux® solar control window films as an integral part of seeking to comply with the CRC Energy Efficiency Scheme and The Carbon Trust policies. It also helps to alleviate the discomfort caused by excessive heat. The film is applied externally and, in daytime, lends the glass a light silver reflective outside appearance, whilst from the inside, the visual effect, much less noticeable, is a light tint.

FEATURES

- Good solar heat rejection
- Cuts energy use for cooling
- Quick, retro-fit installation
- Scratch-resistant
- Screening of harmful UV rays

BENEFITS

- Alleviate the discomfort caused by solar heat gain
- Reducing energy tax liability and contributes to a reduced carbon footprint
- Can be used where costly and disruptive large-scale replacement of existing glazing is not a viable option
- Suitable for most non-abrasive window-cleaning methods

PERFORMANCE DATA		SO-50RS-eSR
SOLAR ENERGY	Transmitted	43%
	Reflected	25%
	Absorbed	32%
VISIBLE LIGHT	Transmitted	59%
	Reflected (Interior)	17%
	Reflected (Exterior)	17%
UV Rejection		99%
Glare Reduction		40%
Shading Coefficient		0.4
Solar Heat Gain Coefficient (G-Value)		0.5
U-Value (W/m²K)		5.8
Total Solar Energy Rejected		53%
Product Warranty		7 years vertical Up to 4 years sloping

NOTES

Test results are produced from film applied to 3mm clear single glass. Performance data is subject to change without prior notice. Accurate selection of window films requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct, indirect or consequential loss or damage howsoever arising.

SPECIFICATION

The solar control window film is to be Opalux® SO-50RS-eSR, as manufactured by Opalux® (www.opaluxwindowfilms.com). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

SOLAR CONTROL